



Benefits

- Easy retrofit replacement
- Long lifespan
- Die-cast aluminum housing for higher power and brightness

|          |         |          |      |      |                   |
|----------|---------|----------|------|------|-------------------|
| 170-240V | CRI ≥80 | -20~40°C | IP20 | IK02 | 3000K/4000K/6500K |
|----------|---------|----------|------|------|-------------------|



| Model         | W  | PF      | lm   | BA   |       | Single Box Dimensions (LxWxH)mm | Outer Box Dimensions (LxWxH)mm | Packing Qty (PCS/CTN) |
|---------------|----|---------|------|------|-------|---------------------------------|--------------------------------|-----------------------|
| YTUFOZ2 30W   | 30 | 0.5/0.9 | 3000 | 120° | 25000 | 132*132*120                     | 548*415*260                    | 24                    |
| YTUFOZ2-L 30W | 30 | 0.5/0.9 | 3000 | 120° | 25000 | 132*132*145                     | 548*415*310                    | 24                    |
| YTUFOZ2 50W   | 50 | 0.5/0.9 | 5000 | 120° | 25000 | 125*145*145                     | 520*455*465                    | 12                    |
| YTUFOZ2-L 50W | 50 | 0.5/0.9 | 5000 | 120° | 25000 | 155*145*145                     | 455*330*310                    | 12                    |

Dimensional Drawing

