




Benefits

- Easy retrofit replacement
- Long lifespan
- High color reproduction
- More energy saving



Size:Ø92*30mm
Cut-out:Ø75mm



Size:92*92*30mm
Cut-out:75*75mm



Size:92*176*30mm
Cut-out:75*150mm



Size:92*255*30mm
Cut-out:75*235mm




170-240V	CRI 80/90	-20~40°C	IP20	GU10	3000K/4000K/6500K
----------	-----------	----------	------	------	-------------------



Model	W	PF	lm	BA	Beam	Single Box Dimensions (LxWxH)mm	Outer Box Dimensions (LxWxH)mm	Packing Qty (M)
YTGU10M1-CL 5W	5	0.5	450/500	24/36°	25000	51*51*60	535*275*135	100
YTGU10M1-CL 7W	7	0.5	630/700	24/36°	25000	51*51*60	535*275*135	100
AL YTGU10M1-CL 8W	8	0.5	720/800	24/36°	25000	51*51*60	535*275*135	100
Dimmable								
YTGU10M1-CL-DIM 7W	7	0.7	630/700	24/36°	25000	51*51*60	535*275*135	100
AL YTGU10M1-CL-DIM 8W	8	0.7	720/800	24/36°	25000	51*51*60	535*275*135	100
Ra > 90								
YTGU10M1-CL 7W	7	0.7	630/700	24/36°	25000	51*51*60	535*275*135	100
AL YTGU10M1-CL 8W	8	0.7	720/800	24/36°	25000	51*51*60	535*275*135	100

Dimensional Drawing



YTGU10M1-CL